

POLYFLOR STANDARD XL

- Hardwearing, homogeneous sheet and tile contract floorcovering
- 16 marbled colourways (2.0mm)

SPECIFICATION

1.5mm, 2.0mm 2.5mm, 3.0mm	608 x 608mm 2.0mm: 5.17m ²
300 x 300mm 2.0mm: 4.5m ² 2.5mm: 3.6m ² 3.0mm: 2.97m ²	1.5mm: 2360g/m ² 2.0mm: 3200g/m ² 2.5mm: 4200g/m ² 3.0mm: 5010g/m ²
1.5mm: 2m x 27.5m = 55m ² 2.0mm: 2m x 20m = 40m ² 2.5mm: 2m x 15m = 30m ² 3.0mm: 2m x 13m = 26m ²	

HOMOGENEOUS

POLYFLOR STANDARD XL

HOMOGENEOUS

PERFORMANCE AND
PROPERTIES

	GENERAL PERFORMANCE	
	EN 649	1.5mm
	ASTM F1913	2.0mm
	ASTM F1700	2.5mm
	Agreement - 1.5mm: G3ws	3.0mm
	2.0, 2.5, 3.0mm: G5ws	

	REACTION TO FIRE	
	EN 13501-1 Class Bfl-S1 (all gauges)	EN ISO 9239-1 ≥8kw/m ² (all gauges)
		EN ISO 11925-2 Pass (all gauges)
	ASTM E662 <450 (1.5, 2.0mm)	
	ASTM E648 Class 1 (1.5, 2.0mm)	

	SLIP RESISTANCE		ABRASION RESISTANCE
	EN 13893 Class DS		EN 649 Group M
	AS/NZS 4586 R9		

	MARITIME USAGE	†2.0mm
	Marine Equipment Directive †	
	96/98/EC as amended 2002/75/EC	
	SOLAS 74	

	HYGIENE
	This product has been independently tested and results demonstrate that it inhibits the growth of MRSA. An effective cleaning regime is however, the most important defence against infection.

	ELECTRICAL BEHAVIOUR (body voltage)
	EN 1815 This product does not accumulate static charges above 2kV and is classified as 'antistatic'. For specialist applications where there is a requirement to dissipate the electrostatic charge, see the Polyflor ESD product ranges. (1.5mm, 2.0mm)

	ENVIRONMENT	
	BRE Green Guide to Specifications A rating*	
	*2.0mm	

	APPLICATIONS
	Polyflor Standard XL is recommended for public, institutional and commercial buildings where long life under heavy traffic is required e.g. hospitals, schools, laboratories, offices etc.

	For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor.
--	--

--	--	--	--

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
 TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128
 EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM
 UK SAMPLE REQUESTS: +44 (0)161 767 2551



1.5mm, 2.0mm	2.5mm, 3.0mm
05	05
EN 14041:2004	EN 14041:2004
EN 649	EN 649

