

POLYFLEX VC TILE

- General purpose vinyl composition tile
- Through-chip manufacture for durability and life-long appearance retention

SPECIFICATION



2.0mm



55 @ 300 x 300mm = 4.95m²



4400g/m²



GENERAL PERFORMANCE

EN 654



REACTION TO FIRE

EN 13501-1 Class Bfl-S1 { EN ISO 9239-1 $\geq 8\text{kw/m}^2$
EN ISO 11925-2 Pass



SLIP RESISTANCE

EN 13893 Class DS



ELECTRICAL BEHAVIOUR (body voltage)

EN 1815 This product does not accumulate static charges above 2kV and is classified as 'antistatic'. For specialist applications where there is a requirement to dissipate the electrostatic charge, see the Polyflor ESD product ranges.



DIMENSIONAL STABILITY

EN 654



FLEXIBILITY

EN 654



INDENTATION - RESIDUAL

EN 654



APPLICATIONS

Polyflex VC Tile is suitable for areas with moderate commercial traffic that require an attractive and economical floorcovering.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor. At the date of issue the data presented is correct. However, Polyflor Ltd. reserve the right to make changes which do not adversely affect performance or quality.



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM
UK SAMPLE REQUESTS: 0161 767 2551

James Halstead
FLOORING

POLYFLOR

POLYFLEX VC TILE

SEMI FLEXIBLE TILES

PERFORMANCE AND PROPERTIES


POLYFLOR
COVERING THE WORLD