

SAARFLOOR SLATE

- Heavy contract, synthetic rubber floor tiles
- Slate profile surface finish
- Durability and comfort with the classic look of natural slate

SPECIFICATION



3.5mm



18 @ 500 x 500mm = 4.5m²



5100g/m²



GENERAL PERFORMANCE

EN 12199



REACTION TO FIRE

EN 13501-1 Class Cfl-S1

EN ISO 9239-1 ≥4.5kw/m²

EN ISO 11925-2 Pass



CIGARETTE RESISTANCE

EN 1399

Method A Rating >4

Method B Rating >3



SLIP RESISTANCE

EN 13893 Class DS



ACOUSTICAL IMPACT SOUND REDUCTION

EN ISO 140-8

Rubber floors make a beneficial contribution to impact sound reduction.



APPLICATIONS

SaarFloor-Systems Slate is suitable for very heavy commercial use in areas of high public circulation such as shopping malls, train stations, airports, department stores, hospitals and educational establishments and other public buildings.

Prolonged exposure to oil, grease and fats causes deterioration.

SaarFloor-Systems Slate is suitable for areas where spillage is infrequent, but not garage workshops or food preparation areas.

SaarFloor-Systems Slate is not recommended for exterior use or swimming pool surrounds.




For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor.



SLATE

PERFORMANCE AND PROPERTIES



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
 TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128
 EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM
 UK SAMPLE REQUESTS: +44 (0)161 767 2551

James Halstead
FLOORING



January 2007

