

SAARFLOOR STAR

- Heavy contract, synthetic rubber sheet floorcovering
- Non-directional duotone decoration
- Embossed surface finish

SPECIFICATION



2.0mm



1.90m x 10m = 19m²



3200g/m²



GENERAL PERFORMANCE

EN 1817



REACTION TO FIRE

EN 13501-1 Class Cfl-S1
EN ISO 9239-1 ≥4.5kw/m²
EN ISO 11925-2 Pass



CIGARETTE RESISTANCE

EN 1399 Method A Rating >4
Method B Rating >3



SLIP RESISTANCE

EN 13893 Class DS



ACOUSTICAL IMPACT SOUND REDUCTION

EN ISO 140-8
Rubber floors make a beneficial contribution to impact sound reduction.



APPLICATIONS
SaarFloor-Systems Star is especially recommended for public, institutional and commercial buildings where ease of maintenance and long life under heavy traffic are required. Prolonged exposure to oil, grease and fats causes deterioration. SaarFloor-Systems Star is suitable for areas where spillage is infrequent, but not garage workshops or food preparation areas. SaarFloor-Systems Star is not recommended for exterior use or swimming pool surrounds.




For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor.



STAR

PERFORMANCE AND PROPERTIES



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM
UK SAMPLE REQUESTS: +44 (0)161 767 2551

James Halstead
FLOORING

