

## SPORT67 SPORT80

- Heavy-duty, flexible vinyl sheet sports flooring
- Designed to perform safely and effectively in 'multi-purpose' indoor sports venues
- 6 plain colours and maple wood effect

### SPECIFICATION



6.7mm  
8.0mm



2m x 18m = 36m<sup>2</sup>\*  
2m x 15m = 30m<sup>2</sup>\*



Plain colours 4260g/m<sup>2</sup>  
Plain colours 4560g/m<sup>2</sup>



Maple 4510g/m<sup>2</sup>  
Maple 4610g/m<sup>2</sup>



#### GENERAL PERFORMANCE

Tested in accordance with BS 7044 and European standards for sports floorings as given below

#### BALL REBOUND RESILIENCE

**BS 7044** Tennis Ball Pass  
Netball Pass  
Basketball Pass  
Football Pass

#### PEAK DECELERATION

**BS 7044** energy absorbing†

#### VELOCITY CHANGE OF ROLLING BALL

**BS 7044** Pass

#### TRACTION

**BS 7044** Pass

#### COLOUR TRANSFER

**BS 7044** Pass



#### REACTION TO FIRE

**EN 13501-1** Class Cfl-S1 { **EN ISO 9239-1** ≥4.5kw/m<sup>2</sup>  
**EN ISO 11925-2** Pass



#### SLIP RESISTANCE

**EN 13893** Class DS  
**BS 7044** Pass



#### ABRASION RESISTANCE

**EN 660-2** Group T



#### ABRASION RESISTANCE TO ABRASIVE WHEELS

**BS 7044** Pass



#### RESISTANCE TO INDENTATION

**BS 7044** Pass



#### COLOUR FASTNESS

**ISO 105-B02** Method 3 >6



#### LIGHT REFLECTANCE VALUES

**ISO 2813** ≤30



#### DIMENSIONAL STABILITY

**EN 434** Pass



#### ELECTRICAL BEHAVIOUR (BODY VOLTAGE)

**EN 1815** This product does not accumulate static charges above 2kV and is classified as 'antistatic'.



#### BIOACTIVITY

Will not support the growth of bacteria and fungi.



#### APPLICATIONS

Polyflor Sport is recommended for use in school and local authority sports halls, gymnasias and leisure centres where a degree of resilience underfoot and long life under heavy traffic are needed.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor.

\* Available in non-standard lengths from 15m to 23m in increments of 1 whole metre, consult Polyflor for details.

† Installed on cradle and batten subfloor.



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK  
TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128  
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM  
UK SAMPLE REQUESTS: +44 (0)161 767 2551

*James Halstead*  
FLOORING

**POLYFLOR**  
COVERING THE WORLD